

Mercedes-Benz Lebanon

Tel: +961 9 447444



Mercedes-Benz

Trucks you can trust

2018 Mercedes-Benz Actros
Actros 4148K/ 4200 / 8x4

[Price \\$100,000](#)

Features:



Specification:

Registration Number	J0304537
Registration Date	2018
Odometer	N/A
Exterior Colour	MB9147
Transmission	Manual
Fuel Type	Diesel
Engine Size	15.5 L
Body Style	TIPPER CHASSIS

Additional Description:

Weight variant 41.0 t (7.5/7.5/13.0/13.0) Single-cylinder air compressor, non-regulated Radiator protection, bottom Fuel preheating system Engine brake with constantly open throttle valve Fuel pre-filter, heated water separator Tandem air cleaner system Protective plate under radiator and engine Engine number, stamped-in Engine mountings, for off-road use Insect screen, in front of cooling system High-speed fan, with belt drive Engine cooling power, increased Engine version, Euro II Engine, V8, LA, 350 kW (476 hp), 1800 rpm Clutch, reinforced Transmission G 240-16/11.7-0.69 Gearshift, hydraulic Transmission oil cooling PTO, layshaft MB 131-2c Differential lock rear axle Front axle load compensating system Stabilizer front axle Front axle, straight version Front axle 7.5 t Rear axle H7, 13.0 t, crown wheel 300 Axle ratio $i = 5.849$ (HL7) Stabiliser, rear axle, under frame Front spring, 7.5 t, hard Rear spring, 16.0 t, hard Wheel nut cap 15-degree tapered rims, 9.00 x 22.5 Spare wheel carrier, provisional Spare wheel/spare wheel rim 1.A.308K17 75 2x 13 R 22,5 Highway Bridgestone R 187 2.A.308K17 75 2x 13 R 22,5 Highway Bridgestone R 187 3.A.308L79 75 4x 13 R 22,5 Traction (M+S) Bridgestone M729 4.A.308L79 75 4x 13 R 22,5 Traction (M+S) Bridgestone M729 308K17 75 1x 13 R 22,5 Highway Bridgestone R 187 Implement carrier, left Bumper, steel version Rear underride guard (EC) Steering LS 6/LS 8 Tank-cap lock Screen, tank filler neck Exhaust silencer(s), vertical, behind cab Main tank, 300 l, aluminium Wing, for chassis transit Trailer/tow-away coupling, Ringfeder Tow-away coupling, rear Dual-circuit full air brakes Automatic brake adjusting Compressed-air drier (single-chamber system) Roll back prevention Voith retarder, performance optimised Anti-lock braking system (ABS), disengageable Drum brakes on front and rear axle Telligent braking system with ABS and ASR Wide-angle exterior mirror on front passenger side Electrical adjustable, heated rearview mirrors Ramp mirror on co-driver's side Central locking system Roof hatch/vent, roof S cab Cab rear wall, straight Cab rear wall with window Sun visor, exterior, transparent Windows, tinted, without sun filter Cab steps, movable Cab mountings, rear, reinforced Cab mountings, standard Wide-angle mirror on driver's side, heated Exterior rear-view mirror, grooved cover Deletion, immobiliser (transponder) Front mirror, aerodynamic Air horns, cab roof Steering column-rake and height adj. w. pneum lock multi-function steering wheel Air controlled heating/ventilation system Outside temperature gauge Telligent Maintenance System Fuel consumption display Additional socket, 24 V/15 A, firewall Voltage transformer, 24 V/12 V, 15 A CD-radio Provision for fitting CB radio Power windows for driver's/co-driver's door Floor mat, rubber, driver's and co-driver's side Distribution cockpit Pre-installation for refrigerator box Air conditioning system Construction-site filter Speedometer, km Instrument cluster, graphics-capable display Reversing warning device Fold-up seat, co-driver Driver's standard suspension seat, Isringhausen Batteries 2x12V 165 AH 6-part tail light cluster with reflector Headlamp range adjuster Headlamp unit, H7, with clear-lens look Indicator transmitter for extra indicator lamps Alternator 28 V / 80 A Battery box, lockable Fog lamps, halogen Protective grilles, headlamps Position lamps, top, yellow Rotating beacon, yellow, left+right, front Cruise control Speed limiter, electronic, 85 km/h Tools for export Labels/publications, English Publications, Arabic, additional Actros 3 Deletion, noise reduction measures First aid kit Fire extinguisher 2 wheel chocks Tyre inflating hose, 25 m Hazard warning triangle Warning lamp Hand lamp, 10 m cable Jack, 25 t Compressed-air gun, supplied loose Tyre pressure tester, digital Country-specific version Vehicle, for right-side traffic Spring brake cylinder on the 2. Front axle

We make every effort to ensure that the information contained on this specification sheet is accurate and complete. However, errors and omissions may occur from time to time and we are not able to guarantee the accuracy of the information.